

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 11

SDS No.: 592717 V003.0

Revision: 04.01.2022

printing date: 05.01.2022

Replaces version from: 19.02.2019

UniBond PL200 White

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifler

UniBond PL200 White

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Assembly adhesive, reaction

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589

Düsseldorf

Germany

Phone:

+49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains: Trimethoxyvinylsilane May produce an allergic reaction.

recautionary statement: P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P262 Do not get in eyes, on skin, or on clothing.

2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | CAS-No. REACH-Reg No. | | Classification | | |
|------------------------------------|-------------------------------|----------|--------------------------|--|--|
| Trimethoxyvinylsilane 2768-02-7 | 220-449-8 01-2119513215-52 | 0,1-< 1% | Flam. Liq. 3 H226 | | |
| | | | Acute Tox. 4; Inhalation | | |
| | | | STOTRE 2 H373 | | |
| | | | Skin Sent, 18 H317 | | |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Temperatures between + 5 °C and + 35 °C

Store in a cool, dry place.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Assembly adhesive, reaction

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

| Ingredient [Regulated substance] | bbur | mg/m³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|----------------------------------|------|-------|-----------------------|--|-----------------|
| Limestone | | 10 | Time Weighted Average | | EH40 WEL |
| 1317-65-3 | | | (TWA): | | |
| [CALCIUM CARBONATE, INHALABLE | | | | | |
| DUST] | ļ | l | ļ | 1 | |
| Limestone | | 4 | Time Weighted Average | | EH40 WEL |
| 1317-65-3 | | | (TWA): | | |
| [CALCIUM CARBONATE, RESPIRABLE | | | | | 1 |
| DUST] | | ļ | | | 1 |
| Limestone | 1 | 4 | Time Weighted Average | Ţ | EH40 WEL |
| 1317-65-3 | | ļ | (TWA): | 1 | |
| [LIMESTONE, RESPIRABLE | | - | } | + | |
| MARBLE, RESPIRABLE] | | | | | Brida Mari |
| Limestone | i | 10 | Time Weighted Average | | EH40 WEL |
| 1317-65-3 | i | | (TWA): | | |
| [LIMESTONE, TOTAL INHALABLE | | | | | |
| MARBLE, TOTAL INHALABLE] | | | | | |
| Methanol | | | Skin designation: | Can be absorbed through the | EH40 WEL |
| 57-56-1 | | | | skin. | |
| [METHANOL] | ļ | Į | 1 | | |
| Methanol | 200 | 266 | Time Weighted Average | | EH40 WEL |
| 67-56-1 | | | (TWA): | | |
| [METHANOL] | ļ | ļ | | | r.com. 17 |
| Methanol | 200 | 260 | Time Weighted Average | Indicative | ECTLV |
| 67-56-1 | | İ | (TWA): | | 1 |
| [METHANOL] | | ļ | | 1 | |
| Methanol | 250 | 333 | Short Term Exposure | 15 minutes | EH40 WEL |
| 67-56-1 | | | Limit (STEL): | | 1 |
| [METHANOL] | | | | | 1 |
| Di-"isononyl" phthalate | | 5 | Time Weighted Average | | EH40 WEL |
| 28553-12-0 | | | (TWA): | | |
| [DIISONONYL PHTHALATE] | l | | | | |

Occupational Exposure Limits

Valid for Ireland

| Ingredient [Regulated substance] | ppm | mg/m³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------|------------------------------|--|-----------------|
| Limestone 1317-65-3 | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| [CALCIUM CARBONATE] Limestone 1317-65-3 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Methanol 67-56-1 | 200 | 260 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| [METHANOL] Methanol 67-56-1 [METHANOL] | | | Skin designation: | Can be absorbed through the skin. | IR_OEL |
| Methanol 67-56-1 [METHANOL] | 200 | 260 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Di-"isononyl" phthalate 28553-12-0 [DISONONYL PHTHALATE] | | 5 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on iist | Environmental Compartment | Exposure period | Value | | Remarks | | |
|------------------------------------|------------------------------------|--------------------|-----------|-----|------------|--------|--|
| | | | mg/l | ppm | mg/kg | others | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (freshwater) | | 0,4 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | aqua (marine water) | | 0,04 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | Freshwater - intermittent | | 1,21 mg/l | | | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (freshwater) | | | | 1,5 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (marine water) | | | | 0,15 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | Soil | | | | 0,06 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | sewage treatment plant (STP) | | 6,6 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|------------------------------------|-----------------------|----------------------|---|------------------|------------|---------|
| Trimethoxyvinylsilane 2768-02-7 | Workers | dermal | Long term exposure - systemic effects | | 3,9 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | inhalation | Long term exposure - systemic effects | | 27.6 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | dermal | Long term exposure - systemic effects | ! | 7,8 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | General population | inhalation | Long term exposure - systemic effects | | 6,7 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | oral | Long term exposure - systemic effects | | 0,3 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance paste pasty

pasty beige

Odor alcohol-like

Odour threshold No data available / Not applicable

pН

Melting point Solidification temperature Initial boiling point Flash point Evaporation rate Flammability Explosive limits

Vapour pressure Relative vapour density:

Density

(20°C (68 °F)) Bulk density Solubility

Solubility (qualitative)

(23 °C (73.4 °F); Solvent: Water) Partition coefficient: n-octanol/water

Auto-ignition temperature Decomposition temperature

Viscosity

(; 40 °C (104 °F)) Viscosity (kinematic) Explosive properties Oxidising properties

Not available.

No data available / Not applicable No data available / Not applicable Not available. 94 °C (201.2 °F); no method No data available / Not applicable
1,63 g/cm3

No data available / Not applicable No data available / Not applicable

Miscible

No data available / Not applicable No data available / Not applicable No data available / Not applicable

Not available.

No data available / Not applicable No data available / Not applicable No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Evolves methanol during cure.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|---------------|-------------|---------|--|
| Trimethoxyvinylsilane | LD50 | 7.120 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2768-02-7 | l . | I | | <u> </u> |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---------------------------------|---------------|-------------|---------|--|
| Trimethoxyvinylsilane | LD50 | 3.200 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| 2768-02-7 | | | | |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|---------------------------------|---------------|-----------|-----------------|------------------|---------|---------------------------|
| Trimethoxyvinylsilane | LC50 | 16,8 mg/l | vapour | 4 h | rat | OECD Guideline 403 (Acute |
| 2768-02-7 | | _ | | | | Inhalation Toxicity) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|------------------|
| Trimethoxyvinylsilane | not irritating | | rabbit | other guideline: |
| 2768-02-7 | | <u> </u> | | |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------|----------------|------------------|---------|---|
| Trimethoxyvinylsilane | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|------------------------------|-------------|--------------|------------|---|
| Trimethoxyvinylsilane | sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| 2768-02-7 | | | | |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|------------------------------------|----------|--|--|---------|--|
| Trimethoxyvinylsilane 2768-02-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Trimethoxyvinylsilane 2768-02-7 | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Marumalian Cell Gene Mutation Test) |
| Trimethoxyvinylsilane | negative | intraperitoneal | | mouse | other guideline: |

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|------------------------------------|----------------------|-----------------------------|----------------------|---------|---|
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 250 mg/kg | one- generation study | oral: gavage | ral | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL F1 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|------------------------------------|--------------------|-----------------------|--|---------|---|
| Trimethoxyvinylsilane 2768-02-7 | NOAEL < 62,5 mg/kg | oral: gavage | 42d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL 0,605 mg/l | inhalation: vapour | 5 days/week for 14 weeks 6 hours/day | rat | not specified |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|----------|---------------|----------------------|---------------------------|
| Trimethoxyvinylsilane | LC50 | 191 mg/l | 96 h | Outon Julius Mariana | OECD Guideline 203 (Fish, |
| 2768-02-7 | l | | | <u> </u> | Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | 1 | Value | Exposure time | | Method |
|-------------------------------|------|------------|---------------|---------------|-----------------------|
| CAS-No. Trimethoxyvinylsilane | EC50 | 168,7 mg/l | 48 h | Daphnia magna | EU Method C.2 (Acute |
| 2768-02-7 | 1 | 1 | | | Toxicity for Daphnia) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|-----------------------|-------|-----------|---------------|---------|--|
| CAS-No. | type | <u> </u> | | | OFCD 311 (Darbaia |
| Trimethoxyvinylsilane | NOEC | 28,1 mg/l | 121 d | | OECD 211 (Daphnia magna, Reproduction Test) |
| 2768-02-7 | | | | | magna. Reproduction rest) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|------------------------------------|---------------|------------|---------------|-------------------------|--|
| Trimethoxyvinylsilane 2768-02-7 | EC50 | > 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algal Inhibition test) |
| Trimethoxyvinylsilane 2768-02-7 | NOEC | 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algai Inhibition test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|----------------------|--------------|------------|---------------|-------------------------------|--|
| | type EC50 | > 100 mg/l | 3 h | predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

| TIMENT COMP CONTRACT | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|------------------|---|
| CAS-No. Trimethoxyvinylsilane 2768-02-7 | not readily biodegradable. | aerobic | 51% | | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

| Hazardous substances | PBT / vPvB |
|-----------------------|--|
| CAS-No. | |
| Trimethoxyvinylsilane | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 2768-02-7 | Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080410

| | SECTION 14: Transport information | |
|-------|---|--|
| 14.1. | UN number | |
| | Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. | |
| 14.2. | UN proper shipping name | |
| | Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. | |
| 14.3. | Transport hazard class(es) | |
| | Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. | |
| 14.4. | Packing group | |
| | Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR. | |
| 14.5. | Environmental hazards | |
| | TO A DID A DID A DIVINIDO LA TA DOD | |

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable Not applicable Hexachlorobenzene CAS 118-74-1

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.