

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 10

SDS No.: 592649

V001.0 Revision: 31.01.2017

printing date: 23.02.2021 Replaces version from: -

UniBond FT101 Transparent

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

UniBond FT101 Transparent

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, polymer silan-modified

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@uk.henkel.com

## 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### **Classification (CLP):**

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

# Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Precautionary statement: P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

### 2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### General chemical description:

Joint sealants

#### Base substances of preparation:

Diisononyl phthalate

### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Trimethoxyvinylsilane 2768-02-7	220-449-8 01-2119513215-52	1-< 3 %	Flam. Liq. 3 H226 Acute Tox. 4; Inhalation H332
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	247-384-8 01-2119955688-17	0,1-< 1 %	STOT RE 2; Oral H373 Aquatic Chronic 4 H413 ===== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

## 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

### 5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Ensure good ventilation/suction at the workplace.

Avoid skin and eye contact.

### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Store in a cool place.

Storage at 5 to 25°C is recommended.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

#### 7.3. Specific end use(s)

Joint sealant, polymer silan-modified

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Methanol 67-56-1 [METHANOL]	250	333	Short Term Exposure Limit (STEL):		EH40 WEL
Methanol 67-56-1 [METHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Methanol 67-56-1 [METHANOL]	200	266	Time Weighted Average (TWA):		EH40 WEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV

# **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Methanol 67-56-1 [METHANOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
	Compartment	periou	mg/l	ppm	mg/kg	others	
Trimethoxyvinylsilane 2768-02-7	aqua (freshwater)		0,36 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (marine water)		0,036 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (intermittent releases)		2,4 mg/l				
Trimethoxyvinylsilane 2768-02-7	sewage treatment plant (STP)		6,6 mg/l				
Trimethoxyvinylsilane 2768-02-7	sediment (freshwater)				1,3 mg/kg		
Trimethoxyvinylsilane 2768-02-7	sediment (marine water)				0,13 mg/kg		
Trimethoxyvinylsilane 2768-02-7	soil				0,055 mg/kg		
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	aqua (freshwater)		0,01 mg/l				
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	aqua (marine water)		0,001 mg/l				
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	sewage treatment plant (STP)		1 mg/l				
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	aqua (intermittent releases)		0,1 mg/l				
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	soil				90 mg/kg		
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	sediment (freshwater)				451 mg/kg		
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	sediment (marine water)				45,1 mg/kg		
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	oral				13,2 mg/kg		

01.0

### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Trimethoxyvinylsilane 2768-02-7	Workers	dermal Long term exposure - systemic effects			0,2 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	Inhalation	Long term exposure - systemic effects		2,6 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Acute/short term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	Inhalation	Acute/short term exposure - systemic effects		0,7 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Long term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	Inhalation	Long term exposure - systemic effects		0,7 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	oral	Long term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Acute/short term exposure - systemic effects		0,2 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2,6 mg/m3	
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	Workers	dermal	Long term exposure - systemic effects		0,3 mg/kg	
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	Workers	Inhalation	Long term exposure - systemic effects		0,7 mg/m3	
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	General population	dermal	Long term exposure - systemic effects		0,14 mg/kg	
2-(2H-Benzotriazol-2-yl)-4,6- ditertpentylphenol 25973-55-1	General population	Inhalation	Long term exposure - systemic effects		0,17 mg/m3	

### **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Filter: AX (EN 14387)

This recommendation should be matched to local conditions.

### Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection: Protective goggles

Skin protection:

Suitable protective clothing

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance paste

pasty

transparent Odor alcohol-like

Odour threshold No data available / Not applicable

pH Not available. Initial boiling point Not available. Flash point Not available.

Decomposition temperature No data available / Not applicable Vapour pressure No data available / Not applicable

Density 1,1 g/cm3

(20 °C (68 °F))

Bulk density No data available / Not applicable Viscosity No data available / Not applicable Viscosity (kinematic) No data available / Not applicable No data available / Not applicable Explosive properties No data available / Not applicable Solubility (qualitative) Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

#### 9.2. Other information

No data available / Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

None if used for intended purpose.

## 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

None if used for intended purpose.

### 10.5. Incompatible materials

None if used properly.

### 10.6. Hazardous decomposition products

Evolves methanol during cure.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	LD50	7.120 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
2-(2H-Benzotriazol-2-yl)- 4,6-ditertpentylphenol 25973-55-1	LD50	> 7,750 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

#### Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethoxyvinylsilane	LC50	16,8 mg/l	Vapor.	4 h	rat	OECD Guideline 403 (Acute
2768-02-7		_				Inhalation Toxicity)

### Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	LD50	3.540 mg/kg	dermal		rabbit	not specified

# **SECTION 12: Ecological information**

### General ecological information:

Do not empty into drains, soil or bodies of water.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

## 12.1. Toxicity

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Trimethoxyvinylsilane	LC50	191 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
2768-02-7						203 (Fish, Acute
						Toxicity Test)
Trimethoxyvinylsilane	EC50	> 100 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
2768-02-7						202 (Daphnia sp.
						Acute
						Immobilisation
			ļ			Test)
Trimethoxyvinylsilane	EC50	> 100 mg/l	Algae	72 h		OECD Guideline
2768-02-7						201 (Alga, Growth
						Inhibition Test)
Trimethoxyvinylsilane	EC 50	> 2.500 mg/l	Bacteria	3 h		OECD Guideline
2768-02-7						209 (Activated
						Sludge, Respiration
						Inhibition Test)
2-(2H-Benzotriazol-2-yl)-4,6-	EC0	> 100 mg/l	Bacteria	3 h		OECD Guideline
ditertpentylphenol						209 (Activated
25973-55-1						Sludge, Respiration
			1			Inhibition Test)

### 12.2. Persistence and degradability

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		
2-(2H-Benzotriazol-2-yl)-4,6-		aerobic	2 - 8 %	OECD Guideline 301 B (Ready
ditertpentylphenol				Biodegradability: CO2 Evolution
25973-55-1				Test)

### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

MSDS-No.: 592649

V001.0

2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol 25973-55-1 2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol 25973-55-1	> 6,5	4.790		fish	23 °C	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) OECD Guideline 117 (Partition Coefficient (noctanol / water), HPLC Method)
---	-------	-------	--	------	-------	---

#### 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Trimethoxyvinylsilane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2768-02-7	Bioaccumulative (vPvB) criteria.
2-(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
25973-55-1	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

# **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 % (VOCV 814.018 VOC regulation

CH)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.