

Nylon Hammer Fixings



Suitable for

Concrete, natural stone with dense structure, solid brick, sand-lime solid brick, solid block made from lightweight concrete, aircrete, solid panel made from gypsum, vertically perforated brick, sand-lime perforated block, hollow block made from lightweight concrete.

Application

Wall connection or plaster profiles, baseboards, foils, sheet metals, squared timbers, cable and pipe clips, facings, substructures made of wood and metal. A fast solution with simple 'hammer in' fitting.

Material

Manufactured from virgin nylon, the 'hammer in' fixing comes complete with a steel screw nail, being zinc and yellow passivated for corrosion resistance. Fixing is pre-assembled.

Sizes

- M5: 30mm to 50mm
- M6: 30mm to 80mm
- M8: 60mm to 140mm
- M10: 80mm to 160mm

Packaging

In neutral packaging, (own label showing company name, code and bar code can be added). M5, M6 and M8 gauges in boxes of 100, M10 gauge in boxes of 50.



Product Data

Nylon Plug	Size (mm)	Box Quantity	Outer Quantity	Drill Hole	Plug Length (mm)	MaxFixture Thickness (mm)	Min Drill Hole Depth (mm)
M5	30mm	100	3600	5	30	10	30
	40mm	100	2400	5	40	20	30
	50mm	100	2400	6	50	25	35
M6	30mm	100	3600	6	30	10	30
	40mm	100	2400	6	40	20	35
	50mm	100	2400	6	50	25	35
	60mm	100	1600	6	60	35	35
	80mm	100	1600	6	80	55	35
M8	60mm	100	1200	8	60	20	50
	80mm	100	1200	8	80	40	50
	100mm	100	800	8	100	60	50
	120mm	100	800	8	120	80	50
	140mm	100	800	8	140	95	50
M10	80mm	100	900	10	80	35	60
	100mm	100	600	10	100	60	60
	120mm	100	600	10	120	80	60