

Technical Data Sheet	Title: 0055 G/P Masking Tape	
Effective Date: June 2016	Prepared By: Sam Murphy	
Issue Number: 1	Authorised By: David Wlaker	

### **Product Description**

White crepe paper tape with white synthetic rubber resin adhesive.

### **Applications**

Mainly used for paint masking, holding, bundling, and sealing of a vast number of jobs.

### **Features & Benefits**

Provides a good instant adhesion to a wide variety of surfaces

### **Technical Performance**

Description	Units	Value	Test Method
Peel adhesion on steel at 180°	N/cm	3.8	-
Adhesive coating	g/m <sup>2</sup>	22	-
Paper thickness	g/m <sup>2</sup>	59	-
Total thickness	mm	0.120 ±5%	AFERA 5006
Tensile strength	N/cm	>37	AFERA 5004
Elongation at break	%	>3	AFERA 5004
Adhesion to steel plate	N/cm	>3	AFERA 5001
Temp resistance	°c	60	-
Rolling ball tack	cm	<10	PSTC 6

**Declaration of Conformity Information** Not Applicable

**REACH SVHC Status** – NO SHVC present according to candidates list of 17<sup>th</sup> Dec 2015

**RoHS Compliance Status** – Not Applicable

### **Storage Details**

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.