


PENOSIL BUILDING SILICONE 376

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** PENOSIL BUILDING SILICONE 376
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Sealant
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
WOLF GROUP IBÉRICO, SAU
AVDA. BERTRAN GÜELL, 78
08850 GAVÀ - BARCELONA - SPAIN
Phone: +34 936629911
QHSE.es@wolf-group.com
www.wolf-group.com
- 1.4 Emergency telephone number:** 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
GB CLP Regulation:
Classification of this product has been carried out in accordance with GB CLP Regulation.
Skin Sens. 1B: Sensitisation, skin, Category 1B, H317
- 2.2 Label elements:**
GB CLP Regulation:
Warning
- 
- Hazard statements:**
H317 - May cause an allergic skin reaction.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P501: Dispose of the contents and/or its container using the separate collection system in your municipality.
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking.
Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine.
- Substances that contribute to the classification**
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**
Chemical description: Mixture composed of chemical products

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable	Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1: H304; EUH066 - Danger	20 - <30 %
CAS: 22984-54-9	Butan-2-one O,O',O''-(methylsilylidyne)trioxime Eye Irrit. 2: H319; Skin Sens. 1B: H317; STOT RE 2: H373 - Warning	2,5 - <5 %
CAS: Non-applicable	O,O',O''-(methylsilylidyne)trioxime 2-pentanone Acute Tox. 4: H302; Eye Irrit. 2: H319 - Warning	1 - <2,5 %
CAS: 1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	0,1 - <1 %
CAS: 13463-41-7	Pyrithione zinc Acute Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger	0,01 - <0,1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:**Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 5: FIREFIGHTING MEASURES (continued)

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

it is recommended to avoid environmental spillage of both the product and its container

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime CAS: 22984-54-9 EC: 245-366-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.145 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1.02 mg/m³	Non-applicable
O,O',O''-(methylsilyldiyl)trioxime 2-pentanone CAS: Non-applicable EC: 484-460-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.065 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.229 mg/m³	Non-applicable
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.01 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime CAS: 22984-54-9 EC: 245-366-4	Oral	Non-applicable	Non-applicable	0.072 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.072 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.25 mg/m³	Non-applicable
O,O',O''-(methylsilyldiyl)trioxime 2-pentanone CAS: Non-applicable EC: 484-460-1	Oral	Non-applicable	Non-applicable	0.033 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.033 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.057 mg/m³	Non-applicable

PNEC:

Identification					
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime CAS: 22984-54-9 EC: 245-366-4	STP	3.9 mg/L	Fresh water	0.018 mg/L	
	Soil	65.63 mg/kg	Marine water	0.002 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	557.543 mg/kg	
	Oral	0.00322 g/kg	Sediment (Marine water)	55.754 mg/kg	
O,O',O''-(methylsilyldiyl)trioxime 2-pentanone CAS: Non-applicable EC: 484-460-1	STP	2.15 mg/L	Fresh water	0.1 mg/L	
	Soil	0.044 mg/kg	Marine water	0.01 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	0.569 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0.057 mg/kg	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	STP	25 mg/L	Fresh water	0.062 mg/L	
	Soil	0.009 mg/kg	Marine water	0.006 mg/L	
	Intermittent	0.62 mg/L	Sediment (Fresh water)	0.22 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0.022 mg/kg	
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	STP	0.01 mg/L	Fresh water	0.00009 mg/L	
	Soil	1.02 mg/kg	Marine water	0.00009 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	0.009 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0.009 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment


As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection


- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply):	0.01 % weight
V.O.C. density at 20 °C:	0.11 kg/m ³ (0.11 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C: Liquid

Appearance: Paste

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	205 °C
Vapour pressure at 20 °C:	8 Pa
Vapour pressure at 50 °C:	47.58 Pa (0.05 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	970.1 kg/m³
Relative density at 20 °C:	0.97
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20.5 mm²/s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	300 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS: Non-applicable	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Butan-2-one O,O',O''-(methylsilyldiyl)trioxime CAS: 22984-54-9	LD50 oral	2247 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
O,O',O''-(methylsilyldiyl)trioxime 2-pentanone CAS: Non-applicable	LD50 oral	1234 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Pyrrithione zinc CAS: 13463-41-7	LD50 oral	221 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	0.14 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	112181.82 mg/kg (Calculation method)	0 %
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:**Acute toxicity:**

Identification	Concentration		Species	Genus
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	LC50	597 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	81 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	8.8 mg/L (72 h)	Selenastrum capricornutum	Algae
Pyrrithione zinc CAS: 13463-41-7	LC50	0.003 mg/L (96 h)	Pimephales promelas	Fish
	EC50	0.008 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

Chronic toxicity:

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Pyrithione zinc	NOEC	Non-applicable		
CAS: 13463-41-7	NOEC	0.022 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
N-(3-(trimethoxysilyl)propyl)ethylenediamine	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1760-24-3	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	39 %

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	Non dangerous

Type of waste:

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

- CONTINUED ON NEXT PAGE -

PENOSIL BUILDING SILICONE 376

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Repr. 1B: H360D - May damage the unborn child.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

Classification procedure:

Skin Sens. 1B: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

- CONTINUED ON NEXT PAGE -

Safety data sheet
According to UK REACH

PENOSIL BUILDING SILICONE 376

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -