

TECHNICAL DATA SHEET

PENOSIL Multipurpose Wipes 943

Multipurpose industrial cleaning wipes for the removal of construction chemistry and finishing agent residues from hands, tools, and various surfaces.

Main benefits

- Quick and efficient
- For hands, tools, clothes and surfaces
- Easy to use

Fields of application

Removal of uncured polyurethane foam, silicone, paint, glue, oil and other substances from hands, tools and surfaces. Cleaning and refreshing of old painted surfaces and connection joints.

Application instructions

Application conditions

For better results, remove all stains immediately. The product might not remove fully dried stains. Before using the product, test its compatibility with the material. Close the pot tightly every time after use.

Application method

Pull the cap off, remove the foil insulation, and pull the top end of the wipe from the middle of the roll by guiding it through the opening in the cover. Place the cover back to the pot and tear off the wipe from the perforated area. Leave the end of the next wipe in the plug and close tightly.

Technical data

Properties	Value	Unit
Flash point	41	°C
pH	Neutral	

Colour

White

Package

Plastic tube - 100 wipes in the tube.

Storage conditions and shelf life

Storage time 24 months when stored in a closed package and dry places at temperatures +5 °C to +30 °C.

Limitations

- Not suitable for some plastics, delicate surfaces, and textiles as it may remove or bleach the colour.
- Due to the wide variety of possible substrates, we recommend a preliminary compatibility test.

PENOSIL

We save energy /  Wolf Group

www.penosil.com

Wolf Group Head Office

Suur-Paala 10
13619 Tallinn
Estonia

tel +372 605 9300
fax +372 605 9315
info@penosil.com

Safety regulations

Keep out of the reach of children. Keep out of heat sources and open flame. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if symptoms persist.

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice. This TDS replaces and supersedes all previous data sheets on the same product.