According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: PENOSIL PLASTERSEAL 650

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Jointing Compound . For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

WOLF GROUP IBERICO S.A.U AVDA. BERTRAN GÜELL, 78 08850 GAVÀ - BARCELONA - SPAIN

Phone: +34 936629911 QHSE.es@wolf-group.com www.wolf-group.com

1.4 Emergency telephone number: 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Hazard statements:

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P273: Avoid release to the environment.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, 3-iodo-2-propynyl Butylcarbamate, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of acrylic resin

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	
CAS:		3-iodo-2-propynyl Butylcarbamate Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger	0,1 - <1 %
CAS:	2634-33-5	1,2-benzisothiazol-3(2H)-one Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	0,01 - <0,1 %

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 1/11

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification	Chemical name/Classification	Concentration
CAS:	55965-84-9	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<0,01 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification		M-factor	
3-iodo-2-propynyl Butylcarbamate		10	
CAS: 55406-53-6		1	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		100	
CAS: 55965-84-9	Chronic	100	

Identification	Specific concentration limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5	% (w/w) >=0,05: Skin Sens. 1 - H317
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
3-iodo-2-propynyl Butylcarbamate	LD50 oral	1100 mg/kg	Rat
CAS: 55406-53-6	LD50 dermal	Not relevant	
	LC50 inhalation	3 mg/L (ATEi)	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Not relevant	
	LC50 inhalation	Not relevant	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87.12 mg/kg	Rabbit
	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 2/11

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 4: FIRST AID MEASURES (continued)

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media: 5.1

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 **Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

64 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 3/11

PENOSIL PLASTERSEAL 650

SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
3-iodo-2-propynyl Butylcarbamate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 55406-53-6	Dermal	Not relevant	Not relevant	2 mg/kg	Not relevant
EC: 259-627-5	Inhalation	0.07 mg/m ³	1.16 mg/m³	0.023 mg/m³	1.16 mg/m³
1,2-benzisothiazol-3(2H)-one	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 2634-33-5	Dermal	Not relevant	Not relevant	0.966 mg/kg	Not relevant
EC: 220-120-9	Inhalation	Not relevant	Not relevant	6.81 mg/m³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 2634-33-5	Dermal	Not relevant	Not relevant	0.345 mg/kg	Not relevant
EC: 220-120-9	Inhalation	Not relevant	Not relevant	1.2 mg/m³	Not relevant

PNEC:

Identification					
3-iodo-2-propynyl Butylcarbamate	STP	0.44 mg/L	Fresh water	0.001 mg/L	
CAS: 55406-53-6	Soil	0.005 mg/kg	Marine water	0 mg/L	
EC: 259-627-5	Intermittent	0.001 mg/L	Sediment (Fresh water)	0.017 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.002 mg/kg	
1,2-benzisothiazol-3(2H)-one	STP	1.03 mg/L	Fresh water	0.00403 mg/L	
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0.000403 mg/L	
EC: 220-120-9	Intermittent	0.0011 mg/L	Sediment (Fresh water)	0.0499 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.00499 mg/kg	

8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 4/11

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low -density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure Standards		Emergency measure	Standards
•	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 1.4 % weight

V.O.C. density at 20 °C: 18.04 kg/m³ (18.04 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 5/11





PENOSIL PLASTERSEAL 650

SEC	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)						
	Appearance:	Paste					
	Colour:	White					
	Odour:	Not available					
	Odour threshold:	Not relevant *					
	Volatility:						
	Boiling point at atmospheric pressure:	210 °C					
	Vapour pressure at 20 °C:	115 Pa					
	Vapour pressure at 50 °C:	634.6 Pa (0.63 kPa)					
	Evaporation rate at 20 °C:	Not relevant *					
	Product description:						
	Density at 20 °C:	1288.4 kg/m³					
	Relative density at 20 °C:	0.44					
	Dynamic viscosity at 20 °C:	Not relevant *					
	Kinematic viscosity at 20 °C:	Not relevant *					
	Kinematic viscosity at 40 °C:	>20.5 mm²/s					
	Concentration:	Not relevant *					
	pH:	Not relevant *					
	Vapour density at 20 °C:	Not relevant *					
	Partition coefficient n-octanol/water 20 °C:	Not relevant *					
	Solubility in water at 20 °C:	Not relevant *					
	Solubility properties:	Not relevant *					
	Decomposition temperature:	Not relevant *					
	Melting point/freezing point:	Not relevant *					
	Flammability:						
	Flash Point:	Non Flammable (>60 °C)					
	Flammability (solid, gas):	Not relevant *					
	Autoignition temperature:	201 °C					
	Lower flammability limit:	Not relevant *					
	Upper flammability limit:	Not relevant *					
	Particle characteristics:						
	Median equivalent diameter:	Non-applicable					
9.2	Other information:						
	Information with regard to physical hazard classes						
	Explosive properties:	Not relevant *					
	Oxidising properties:	Not relevant *					
	Corrosive to metals:	Not relevant *					
	Heat of combustion:	Not relevant *					
	Aerosols-total percentage (by mass) of flammable components:	Not relevant *					
	Other safety characteristics:						
	Surface tension at 20 °C:	Not relevant *					
	Refraction index:	Not relevant *					
	*Not relevant due to the nature of the product, not providing inform	nation property of its hazards.					

SECTION 10: STABILITY AND REACTIVITY

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced **Page 6/11**

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 10: STABILITY AND REACTIVITY (continued)

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable Not applicable		Not applicable	Not applicable	Not applicable

Incompatible materials:

Acids Water		Oxidising materials	Combustible materials	Others	
	Avoid strong acids Not applicable Avoid direct impact		Avoid direct impact	Not applicable	Avoid alkalis or strong bases

Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Glass, oxide, chemicals (1)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 7/11

PENOSIL PLASTERSEAL 650

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
3-iodo-2-propynyl Butylcarbamate	LD50 oral	1100 mg/kg	Rat
CAS: 55406-53-6	LD50 dermal	2100 mg/kg	Rabbit
	LC50 inhalation	3 mg/L (ATEi)	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87.12 mg/kg	Rabbit
	LC50 inhalation	0.33 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix):

	Ingredient(s) of unknown toxicity	
Oral	>5000 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	2040.82 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
3-iodo-2-propynyl Butylcarbamate	LC50	0.07 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 55406-53-6	EC50	0.09 mg/L (96 h)	Mysidopsis bahia	Crustacean
	EC50	0.05 mg/L (72 h)	Scenedesmus subspicatus	Algae
1,2-benzisothiazol-3(2H)-one	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 2634-33-5	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 8/11

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
3-iodo-2-propynyl Butylcarbamate	NOEC	0.0084 mg/L	Pimephales promelas	Fish
CAS: 55406-53-6	NOEC	0.0499 mg/L	Daphnia magna	Crustacean

Persistence and degradability: 12.2

Substance-specific information:

Identification	Degradability		Biodegradab	ility
1,2-benzisothiazol-3(2H)-one	BOD5	Not relevant	Concentration	100 mg/L
CAS: 2634-33-5	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
3-iodo-2-propynyl Butylcarbamate	BCF	36	
CAS: 55406-53-6	Pow Log	2.4	
	Potential	Moderate	
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
	Potential	Low	

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
	It is not possible to assign a specific code, as it depends on the intended use by the user	Hazardous

Type of waste:

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 9/11

According to UK REACH (S.I. 2019/758)

PENOSIL PLASTERSEAL 650

SECTION 15: REGULATORY INFORMATION (continued)

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays.
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Classification procedure:

Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

- CONTINUED ON NEXT PAGE -

Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 10/11





PENOSIL PLASTERSEAL 650

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Printing: 25/04/2024 Date of compilation: 19/01/2018 Revised: 19/01/2024 Version: 7 (Replaced Page 11/11