

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 11

SDS No.: 592414

V001.0 Revision: 03.02.2017 printing date: 23.02.2021

Replaces version from: -

UniBond 10T, all colours

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

UniBond 10T, all colours

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, silicone

### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@uk.henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### **Classification (CLP):**

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

### 2.2. Label elements

# Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains 3-Aminopropyltriethoxysilane. May produce an allergic reaction.

**Precautionary statement:** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area. MSDS-No.: 592414 UniBond 10T, all colours Page 2 of 11

V001.0

### 2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### General chemical description:

1-Component silicone joint sealant

### Base substances of preparation:

Polydimethyl siloxane

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Trimethoxyvinylsilane 2768-02-7	220-449-8 01-2119513215-52	1-< 3 %	Flam. Liq. 3 H226 Acute Tox. 4; Inhalation H332
3-Aminopropyltriethoxysilane 919-30-2	213-048-4 01-2119480479-24	0,1-< 1 %	Skin Sens. 1 H317 Skin Corr. 1B H314 Acute Tox. 4; Oral H302

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

MSDS-No.: 592414 UniBond 10T, all colours Page 3 of 11

V001.0

### 5.1. Extinguishing media

### Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

### 5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

Danger of slipping on spilled product.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

# Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed.

Store in a cool, dry place.

Temperatures between + 5 °C and + 25 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

# 7.3. Specific end use(s)

Joint sealant, silicone

MSDS-No.: 592414 UniBond 10T, all colours Page 4 of 11

V001.0

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Methanol 67-56-1 [METHANOL]	250	333	Short Term Exposure Limit (STEL):		EH40 WEL
Methanol 67-56-1 [METHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Methanol 67-56-1 [METHANOL]	200	266	Time Weighted Average (TWA):		EH40 WEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV

# **Occupational Exposure Limits**

Valid for Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Methanol	200	260	Time Weighted Average	Indicative OELV	IR_OEL
67-56-1			(TWA):		
[METHANOL]					
Methanol			Skin designation:	Can be absorbed through the	IR_OEL
67-56-1				skin.	
[METHANOL]					
Methanol	200	260	Time Weighted Average	Indicative	ECTLV
67-56-1			(TWA):		
[METHANOL]					

MSDS-No.: 592414 UniBond 10T, all colours Page 5 of 11 V001.0

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
	•		mg/l	ppm	mg/kg	others	
Trimethoxyvinylsilane	aqua		0,36 mg/l				
2768-02-7	(freshwater)						
Trimethoxyvinylsilane 2768-02-7	aqua (marine water)		0,036 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (intermittent releases)		2,4 mg/l				
Trimethoxyvinylsilane 2768-02-7	sewage treatment plant (STP)		6,6 mg/l				
Trimethoxyvinylsilane 2768-02-7	sediment (freshwater)				1,3 mg/kg		
Trimethoxyvinylsilane 2768-02-7	sediment (marine water)				0,13 mg/kg		
Trimethoxyvinylsilane 2768-02-7	soil				0,055 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	aqua (freshwater)		0,33 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	aqua (marine water)		0,033 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	aqua (intermittent releases)		3,3 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	soil				0,05 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	sewage treatment plant (STP)		13 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	sediment (freshwater)				1,2 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	sediment (marine water)				0,12 mg/kg		

UniBond 10T, all colours

MSDS-No.: 592414 V001.0

# $\label{eq:Derived No-Effect Level (DNEL): Policy of the property of the prop$

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Long term exposure - systemic effects		0,2 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	Inhalation	Long term exposure - systemic effects		2,6 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Acute/short term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	Inhalation	Acute/short term exposure - systemic effects		0,7 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Long term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	Inhalation	Long term exposure - systemic effects		0,7 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	oral	Long term exposure - systemic effects		0,1 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Acute/short term exposure - systemic effects		0,2 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2,6 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	Workers	dermal	Acute/short term exposure - systemic effects		8,3 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	Inhalation	Acute/short term exposure - systemic effects		59 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	Inhalation	Long term exposure - systemic effects		59 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	General population	oral	Acute/short term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	Inhalation	Acute/short term exposure - systemic effects		17,4 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	General population	oral	Long term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	Inhalation	Long term exposure - systemic effects		17 mg/m3	

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Respiratory protection: Suitable breathing mask when there is inadequate ventilation.

Filter: AX (EN 14387)

This recommendation should be matched to local conditions.

MSDS-No.: 592414 UniBond 10T, all colours Page 7 of 11

V001.0

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection: Protective goggles

Skin protection:

Suitable protective clothing

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid pasty

varied, according to

coloration

Odor typical

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Initial boiling point No data available / Not applicable
Flash point No data available / Not applicable
Decomposition temperature No data available / Not applicable
Vapour pressure No data available / Not applicable

Density 1,01 g/cm<sup>3</sup>

(20 °C (68 °F))

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

None if used for intended purpose.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

None if used for intended purpose.

MSDS-No.: 592414 UniBond 10T, all colours Page 8 of 11

V001.0

### 10.5. Incompatible materials

None if used properly.

### 10.6. Hazardous decomposition products

Evolves methanol during cure.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

# General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### Sensitizing:

An allergic reaction cannot be excluded after repeated skin contact.

### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Trimethoxyvinylsilane	LD50	7.120 mg/kg	oral		rat	OECD Guideline 401 (Acute
2768-02-7						Oral Toxicity)
3-	LD50	1.457 mg/kg	oral		rat	OECD Guideline 401 (Acute
Aminopropyltriethoxysila						Oral Toxicity)
ne						-
919-30-2						

# Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	LC50	16,8 mg/l	Vapor.	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

# Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Trimethoxyvinylsilane 2768-02-7	LD50	3.540 mg/kg	dermal		rabbit	not specified
3- Aminopropyltriethoxysila	LD50	4.076 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
ne 919-30-2						

# Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
3-	corrosive	4 h	rabbit	Draize Test
Aminopropyltriethoxysila				
ne				
919-30-2				

# Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
3-	highly irritating		rabbit	not specified
Aminopropyltriethoxysila				
ne				
919-30-2				

MSDS-No.: 592414 UniBond 10T, all colours Page 9 of 11

V001.0

# Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
3-	sensitising	Buehler	guinea pig	OECD Guideline 406 (Skin
Aminopropyltriethoxysila		test		Sensitisation)
ne				
919-30-2				

# **SECTION 12: Ecological information**

# General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains, soil or bodies of water.

# 12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Trimethoxyvinylsilane	LC50	191 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
2768-02-7						203 (Fish, Acute
						Toxicity Test)
Trimethoxyvinylsilane	EC50	> 100 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
2768-02-7						202 (Daphnia sp.
						Acute
						Immobilisation
			1			Test)
Trimethoxyvinylsilane	EC50	> 100 mg/l	Algae	72 h		OECD Guideline
2768-02-7						201 (Alga, Growth
						Inhibition Test)
Trimethoxyvinylsilane	EC 50	> 2.500 mg/l	Bacteria	3 h		OECD Guideline
2768-02-7						209 (Activated
						Sludge, Respiration
	1.050	024 /	T. 1	0.61	<b>D</b> 1 1 · · · ·	Inhibition Test)
3-Aminopropyltriethoxysilane	LC50	> 934 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
919-30-2					Danio rerio)	203 (Fish, Acute
2 4 . 14 . 1	EGG	221 //	D 1 :	40.1	D 1 '	Toxicity Test)
3-Aminopropyltriethoxysilane	EC50	331 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
919-30-2						202 (Daphnia sp.
						Acute Immobilisation
2 A min annony it migth avyy silana	EC50	602 ma/1	A1000	72 h	Coanadasmus subaniastus (novu	Test) OECD Guideline
3-Aminopropyltriethoxysilane 919-30-2	ECSU	603 mg/l	Algae	7 Z II	Scenedesmus subspicatus (new name: Desmodesmus	
919-30-2					subspicatus)	201 (Alga, Growth Inhibition Test)
	NOEC	1,3 mg/l	Algoo	72 h	Scenedesmus subspicatus (new	OECD Guideline
	NOEC	1,5 mg/1	Algae	7211	name: Desmodesmus	201 (Alga, Growth
					subspicatus)	Inhibition Test)
3-Aminopropyltriethoxysilane	EC10	13 mg/l	Bacteria	5 h	subspicatus)	not specified
919-30-2	LCIU	13 111g/1	Dacteria	J 11		not specified

# 12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
3-Aminopropyltriethoxysilane 919-30-2		aerobic	67 %	OECD Guideline 301 A (new version) (Ready Biodegradability:
				DOC Die Away Test)

# 12.3. Bioaccumulative potential / 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	

MSDS-No.: 592414 UniBond 10T, all colours Page 10 of 11

V001.0

Trimethoxyvinylsilane 2768-02-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3-Aminopropyltriethoxysilane	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
919-30-2	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

# **SECTION 14: Transport information**

### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 % (VOCV 814.018 VOC regulation CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 592414 UniBond 10T, all colours Page 11 of 11 V001.0

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

# **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.