

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product name SILOXAMA11 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC1] Adhesives, sealants;

1.3. Details of the supplier of the safety data sheet

Company Siloxa Building Chemicals
Address The Office,
Three Pillars Business Park
Sutton-in-the-Isle,
Cambridgeshire
CB6 2RU
Web www.siloxa.co.uk
Telephone 07977 508633

1.4. Emergency telephone number

Emergency telephone number 07977 508633
Company Siloxa Building Chemicals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008 Flam. Liq. 2: H225; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT SE 3: H335; Aquatic Chronic 3: H412;

2.2. Label elements

Hazard pictograms



Signal Word

Danger

Hazard Statement

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT SE 3: H335 - May cause respiratory irritation.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

2.2. Label elements

Precautionary Statement: Prevention	<p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p> <p>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P272 - Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 - Avoid release to the environment.</p> <p>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
Precautionary Statement: Response	<p>P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 -Immediately call a POISON CENTER/doctor/ .</p> <p>P312 - Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P363 - Wash contaminated clothing before reuse.</p> <p>P370+P378 - In case of fire: Use to extinguish.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 - Store in a well-ventilated place. Keep cool.</p> <p>P405 - Store locked up.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to to hazardous waste collection point. Refer to section 13.1 for waste treatment methods.</p>

2.3. Other hazards

Other hazards	This product does not contain any substances classified as PBT or vPvB.
----------------------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28	50 - 60%	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
Cumene Hydro-Peroxide	617-002-00-8	80-15-9	201-254-7		1 - 10%	Skin Corr. 1B: H314;
2-Methylpropenoic acid (Methacrylic acid)	607-088-00-5	79-41-4	201-204-4	01-2119463884-26	1 - 10%	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314;
1-Hydroxyethylidene-1,1-diphosphonic acid		2809-21-4			0 - 0.5%	Met. Corr. 1: H290; Eye Dam. 1: H318;
Triethyleneglycol Dimethacrylate		109-16-0	203-652-6	01-2119969287-21	1 - 10%	Skin Sens. 1: H317;
Cumene	601-024-00-X	98-82-8	202-704-5		0 - 0.5%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411;
Para-Toluene Sulfo Chloride		000098-59-9			1 - 10%	Met. Corr. 1: H290; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 1: H318;
6,6'-ditert-butyl-4,4'-thiodi-m-cresol (6,6'-Di-tert-butyl-4,4'-thiodi-m-96-6 9-5 -10 -20 cresol)		96-69-5	202-525-2		0 - 0.5%	Skin Sens. 1: H317; Aquatic Chronic 1: H410;
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)		128-37-0	204-881-4	01-2119555270-46	1 - 10%	Aquatic Acute 1: H400; Aquatic Chronic 1: H410;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Keep affected person warm and at rest. <u>get medical attention immediately.</u>
Eye contact	Remove the affected person from the source of contamination immediately. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Immediate medical attention is required.
Skin contact	Remove the affected person from the source of contamination immediately. Remove contaminated clothing. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly. Move the exposed person to fresh air. Keep the affected person warm and at rest. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation of vapour may cause shortness of breath.
Eye contact	May cause irritation to eyes. May cause irritation to mucous membranes.
Skin contact	Irritating to skin.
Ingestion	Ingestion causes burns to the respiratory tract.

4.3. Indication of any immediate medical attention and special treatment needed

	If you feel unwell, seek medical advice (show the label where possible).
--	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO ₂), Dry chemical, Foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Corrosive. . Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	--

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing. In case of fire and/or explosion do
--	---

Print date 2018-06-29

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

5.3. Advice for firefighters

Do not breathe fumes. Control run off water by containing and keeping it out of sewers and watercourses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

6.4. Reference to other sections

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind, keeping bystanders also upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak side up to prevent escape of liquid.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

7.3. Specific end use(s)

Industrial use resulting in manufacture of another substance (use of intermediates). Industrial uses: Uses of substances as such or in preparations at industrial sites.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

8.1.1. Exposure Limit Values

2-Methylpropenoic acid (Methacrylic acid)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40 WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 72 WEL 15 min limit mg/m3: 143 WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
6,6'-ditert-butyl-4,4'-thiodi-m-cresol (6,6'-Di-tert-butyl-4,4'-thiodi-m-9 6-69-5 -10 -20 cresol)	WEL 8-hr limit ppm:- WEL 15 min limit ppm:- WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: 20 WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Butylated Hydroxytoluene (2,6-Di-tert-butyl-p-cresol)	WEL 8-hr limit ppm:- WEL 15 min limit ppm:- WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3:- WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Cumene	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250 WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Methyl methacrylate	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 208 WEL 15 min limit mg/m3: 416 WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Mono ethylene glycol (Ethane-1,2-diol particulate)	WEL 8-hr limit ppm:- WEL 15 min limit ppm:- WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3:- WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Mono ethylene glycol (Ethane-1,2-diol vapour)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40 WEL 8-hr limit mg/m3 total-inhalable dust: WEL 8-hr limit mg/m3 total-respirable dust:	WEL 8-hr limit mg/m3: 52 WEL 15 min limit mg/m3: 104 WEL 15 min limit mg/m3 total-inhalable dust: WEL 15 min limit mg/m3 total-respirable dust:
Para-Toluene Sulfo Chloride	WEL 8-hr limit ppm:- WEL 15 min limit ppm:- WEL 8-hr limit mg/m3 total inhalable dust: WEL 8-hr limit mg/m3 total respirable dust:	WEL 8-hr limit mg/m3:- WEL 15 min limit mg/m3: 5 WEL 15 min limit mg/m3 total inhalable dust: WEL 15 min limit mg/m3 total respirable dust:

DNEL: Derived no-effect level.

Exposure Pattern - Workers

Print date 2018-06-29

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28


Exposure Pattern - Workers

Butylated Hydroxytoluene	Long-term - inhalation - Local effects	5.8 mg/m ³	
	Long-term - dermal - Systemic effects	8.3 mg/kg	
Methyl methacrylate	Acute dermal - Local effects	1500 mg/m ³	
	Long-term - inhalation - Local effects	210 mg/m ³	Long-term - dermal - Local effects 13.67 mg/kg
Mono ethylene glycol	Acute inhalation - Local effects	35 mg/m ³	
	Acute dermal - Systemic effects	106 mg/kg	
Para-Toluene Sulfo Chloride	Long-term - inhalation - Systemic effects	3.5 mg/m ³	
	Long-term - dermal - Systemic effects	0.5 mg/m ³	

Exposure Pattern - General population

Butylated Hydroxytoluene	Long-term - Inhalation - Systemic effects	1.74 mg/m ³	
	Long-term - dermal - Systemic effects	5 mg/kg	
Methyl methacrylate	Acute dermal - Local effects	1500 mg/m ³	
	Long-term - Inhalation - Local effects	74.3 mg/m ³	Long-term - dermal - Local effects 8.2 mg/kg
Mono ethylene glycol	Acute inhalation - Local effects	7 mg/m ³	
	Acute dermal - Systemic effects	53 mg/m ³	

8.2. Exposure controls



8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash immediately with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Eye / face protection

Approved safety goggles. Face shield. Provide eye wash station.

Skin protection - Handprotection

Chemical resistant gloves (PVC). Thickness 0.2mm for periods of 1 - 4hours.Consult with glove manufacturer for break through times.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

9.1. Information on basic physical and chemical properties

Appearance	Gel
Colour	White
Odour	Strong
Odour threshold	No data available
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	= 101 °C
Flash point	= 10 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	= 0.98 (H ₂ O = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	> 500000 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

9.2. Other information

Conductivity	No data available
Gas group	No data available
Benzene Content	Not applicable.
Lead content	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Avoid sparks, flames, heat and sources of ignition.
--	---

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames. Do NOT allow to freeze. Keep away from strong acids, alkalis and organic peroxides/hydroperoxides.
--	--

10.5. Incompatible materials

	Alkalis. Strong acids. Strong oxidising agents.
--	---

10.6. Hazardous decomposition products

	Burning produces irritating, toxic and obnoxious fumes.
--	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Causes severe burns. MAY CAUSE ALLERGIC SKIN REACTION. Irritating to respiratory system.
Skin corrosion/irritation	Causes burns.
Serious eye damage/irritation	CAUSES SEVERE EYE BURNS.

Print date 2018-06-29

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

11.1. Information on toxicological effects

Respiratory or skin sensitisation	May cause sensitisation by skin contact. May cause irritation to respiratory system.
Germ cell mutagenicity	No data is available on this product.
Carcinogenicity	No data is available on this product.
Reproductive toxicity	No data is available on this product.
STOT-single exposure	May cause irritation to respiratory system.
STOT-repeated exposure	No data is available on this product.
Aspiration hazard	No Significant Hazard.

11.1.4. Toxicological Information

2-Methylpropenoic acid	Oral Rat LD50: 1320mg/kg	Dermal Rabbit LD50:500mg/kg
6,6'-ditert-butyl-4,4'-thiodi-m-cresol	Oral Rat LD50: >2000 mg/kg	Dermal Rabbit LD50:>2000 mg/kg
	Inhalation Rat LC50/4 h>5mg/l	
Butylated Hydroxytoluene	Oral Rat LD50: 1700mg/kg Dermal Guinea Pig LD50:>8000mg/kg	Oral Mouse LD50: 800-1600mg/kg
Cumene	Dermal Rat LD50: 12.3mg/kg	Oral Rat LD50: 2910mg/kg
Cumene Hydro-Peroxide	Inhalation Rat LC50/4 h:220ppm	Oral Rat LD50: 382mg/kg
Methyl methacrylate	Dermal Rat LD50: 5000mg/kg	
Mono ethylene glycol	Oral Rat LD50: 4700mg/kg	
Para-Toluene Sulfo Chloride	Oral Rat LD50: 4680mg/kg	Dermal Rabbit LD50:>5010 mg/kg
Triethyleneglycol Dimethacrylate	Oral Mouse LD50:>200mg/kg body weight	

11.1.13. Other information

	Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.
--	--

SECTION 12: Ecological information

12.1. Toxicity

2-Methylpropenoic acid	Daphnia EC50/48h: 130.0000 mg/l	Rainbow trout LC50/96h:85mg/l
6,6'-ditert-butyl-4,4'-thiodi-m-cresol	Daphnia EC50/48h: 0.1600 mg/l	Green algae EC50/96h: 126
Butylated Hydroxytoluene	Daphnia EC50/48h: 0.6100 mg/l Fish LC50/96h: 0.5700 mg/l NOEC / EC10 for marine or -0.3160 mg/l freshwater organisms	Algae IC50/72h: 0.4000 mg/l
Cumene	Fish LC50/96h: 6.3200 mg/l	
Cumene Hydro-Peroxide	Fish LC50/96h: 3.9000 mg/l	
Methyl methacrylate	Daphnia EC50/48h: 69 mg/l Daphnia LC50/48h: 69mg/l	Fish LC50/96h: 130.0000 mg/l Fathead minnows LC50/96h:130mg/l
Para-Toluene Sulfo Chloride	Daphnia EC50/48h: 70.0000 mg/l Algae EC50/72h: >100 Daphnia LC50/48h: >334mg/l	Fish LC50/96h: 100.0000 mg/l Daphnia LC50/24h: >2500mg/l Bacteria EC10/18h: 114mg/l
Triethyleneglycol Dimethacrylate	Daphnia EC50/48h: 100.0000 mg/l	Fish LC50/96h: 16.4 mg/l

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

12.2. Persistence and degradability

	The product is potentially degradable.
--	--

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

Partition coefficient

	SILOXAMA11 Part A	No data available	Para-Toluene Sulfo Chloride	Not relevant
--	-------------------	-------------------	-----------------------------	--------------

12.4. Mobility in soil

No data is available on this product.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

May cause long-term adverse effects in the environment.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations. This material and its container must be disposed of as hazardous waste. Wear suitable protective clothing, gloves and eye/face protection.

Disposal methods

Dispose of this material and its container to hazardous or special waste collection point. Contact a licensed waste disposal company.

Disposal of packaging

Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN2924

14.2. UN proper shipping name

FLAMMABLE LIQUID, CORROSIVE, N.O.S.

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	8
IMDG	3
Subsidiary risk	8
IATA	3
Subsidiary risk	8

14.4. Packing group

Packing group II

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID 338

SILOXAMA11 Part A

Revision 6
Revision date 2018-06-28

ADR/RID

Tunnel Category	(D/E)
-----------------	-------

IMDG

EmS Code	F-E S-C
----------	---------

IATA

Packing Instruction (Cargo)	363
Maximum quantity	5 L
Packing Instruction (Passenger)	352
Maximum quantity	1 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No Chemical safety assessment has been conducted on this product.

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 2 - 2.1.2. Classification - EC 1272/2008. 4 - 4.3. Indication of any immediate medical attention and special treatment needed. 5 - 5.1. Extinguishing media. 8 - Skin protection - Handprotection. 11 - Acute toxicity. 11 - Respiratory or skin sensitisation. 11 - Germ cell mutagenicity. 11 - Carcinogenicity. 11 - Reproductive toxicity. 11 - Serious eye damage/irritation. 11 - STOT-single exposure. 11 - STOT-repeated exposure. 11 - Aspiration hazard. 12 - 12.1. Toxicity. 13 - General information. 13 - Disposal methods. 13 - Disposal of packaging. 15 - 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture. 15 - 15.2. Chemical safety assessment.
Text of Hazard Statements in Section 3	<p>Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Org. Perox. EF: H242 - Heating may cause a fire. Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.</p>

Print date 2018-06-29

SILOXAMA11 Part A**Revision** 6
Revision date 2018-06-28**Other information**

Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Acute Tox. 3: H331 - Toxic if inhaled.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Met. Corr. 1: H290 - May be corrosive to metals.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Acute 1: H400 - Very toxic to aquatic life.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.