

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 9

SDS No.: 592382

V001.0 Revision: 31.01.2017 printing date: 23.02.2021

Replaces version from: -

UniBond 3S, all colours

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

UniBond 3S, all colours

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Joint sealants

# 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@uk.henkel.com

# 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### **Classification (CLP):**

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

### 2.2. Label elements

## Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

**Supplemental information** Contains 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction.

**Precautionary statement:** P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area. MSDS-No.: 592382 UniBond 3S, all colours Page 2 of 9

V001.0

### 2.3. Other hazards

Evolves acetic acid during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### General chemical description:

1-Component silicone joint sealant, acetate-curing (acidic)

### Base substances of preparation:

Polydimethyl siloxane Inorganic fillers

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	265-148-2 01-2119552497-29 01-2119827000-58	20- 40 %	Asp. Tox. 1 H304
2-Octyl-2H-isothiazol-3-one 26530-20-1	247-761-7	50- < 500 PPM	Acute Tox. 3; Inhalation H331 Acute Tox. 3; Dermal H311 Skin Corr. 1B H314 Skin Sens. 1 H317 Aquatic Acute 1 H400 Acute Tox. 4; Oral H302 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

MSDS-No.: 592382 UniBond 3S, all colours Page 3 of 9

V001.0

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

#### Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

### 5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

Danger of slipping on spilled product.

### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed.

Store in a cool, dry place.

Temperatures between + 5  $^{\circ}$ C and + 25  $^{\circ}$ C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

# 7.3. Specific end use(s)

Joint sealants

MSDS-No.: 592382 UniBond 3S, all colours Page 4 of 9

V001.0

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Acetic acid 54-19-7 ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative	ECTLV

# **Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Distillates (petroleum), hydrotreated middle 64742-46-7 [NAPHTA (RUBBER SOLVENT)]				Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), hydrotreated middle 64742-46-7 [MINERAL OIL, PURE, HIGHLY & SEVERELY REFINED, INHALABLE FRACTION]		5	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Acetic acid 64-19-7 [ACETIC ACID]	15	37	Short Term Exposure Limit (STEL):	Indicative OELV	IR_OEL
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative	ECTLV

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation. Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

MSDS-No.: 592382 UniBond 3S, all colours Page 5 of 9

V001.0

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection: Protective goggles

Skin protection:

Suitable protective clothing

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid pasty

varied, according to

coloration

Odor characteristic

Odour threshold No data available / Not applicable

pH No data available / Not applicable Initial boiling point No data available / Not applicable

Flash point Not applicable

Decomposition temperature No data available / Not applicable Vapour pressure No data available / Not applicable

Density 0,97 g/cm3

(20 °C (68 °F))

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

Explosive properties

No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

None if used for intended purpose.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

None if used for intended purpose.

MSDS-No.: 592382 UniBond 3S, all colours Page 6 of 9

V001.0

### 10.5. Incompatible materials

None if used properly.

### 10.6. Hazardous decomposition products

Evolves acetic acid during cure.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

## General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### Sensitizing:

An allergic reaction cannot be excluded after repeated skin contact.

## Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Distillates (Petroleum)	LD50	> 5.000 mg/kg	oral		rat	not specified
hydrotreated middle;						
Gasoil - unspecified						
64742-46-7						
2-Octyl-2H-isothiazol-3-	LD50	318 mg/kg	oral		rat	not specified
one						
26530-20-1						

## Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Distillates (Petroleum) hydrotreated middle;	LC50	> 5,266 mg/l	dust/mist	4 h	rat	not specified
Gasoil - unspecified 64742-46-7						
2-Octyl-2H-isothiazol-3- one 26530-20-1	LC50	0,58 mg/l		4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

# Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2-Octyl-2H-isothiazol-3- one 26530-20-1	LD50	311 mg/kg	dermal		rabbit	not specified

## Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
2-Octyl-2H-isothiazol-3- one 26530-20-1	sensitising	Mouse local lymphnod	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
		e assay (LLNA)		

MSDS-No.: 592382 UniBond 3S, all colours Page 7 of 9

V001.0

# **SECTION 12: Ecological information**

# General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains / surface water / ground water.

## 12.1. Toxicity

Hazardous components CAS-No.	Value	Value	Acute Toxicity	Exposure	Species	Method
CAS-NO.	type		Study	tille		
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	LC50	> 10.000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	LC50	0,036 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
	NOEC	0,022 mg/l	Fish	21 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,42 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,084 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	0,004 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,0016 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

## 12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7		aerobic	30 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1		aerobic	> 83 %	OECD Guideline 303 A (Simulation TestAerobic Sewage Treatment. A: Activated Sludge Units)

### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
2-Octyl-2H-isothiazol-3-one 26530-20-1	2,9					OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)

## 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	

MSDS-No.: 592382 UniBond 3S, all colours Page 8 of 9

V001.0

Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Octyl-2H-isothiazol-3-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
26530-20-1	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

# **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EU) 0,00 %

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 592382 UniBond 3S, all colours Page 9 of 9

V001.0

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.